

Pipes - Fittings

PIPES


> CHAMFERED AT BOTH ENDS, IN 4 METER LENGTHS. WRAPPED IN PLASTIC SLEEVES



DN (Ø ext)	Pipe length (m)	Min. Wall Thickness (mm)	Pack (Lg)	Ref.
16	4	1,8	10*	TUBGA16
20	4	2,3	10*	TUBGA20
25	4	2,8	10*	TUBGA25
32	4	2,9	10*	TUBGA32
40	4	3,7	10*	TUBGA40
50	4	4,6	10*	TUBGA50
63	4	5,8	10*	TUBGA63
75	4	6,8	10*	TUBGA75
90	4	8,2	1	TUBGA90
110	4	10	1	TUBGA110

ELBOWS 90°

> SOCKET/SOCKET



GA4M32

Ø	Pack	Ref.
16	S10*	GA4M16
20	S10*	GA4M20
25	S10*	GA4M25
32	S10*	GA4M32
40	S10*	GA4M40
50	S10*	GA4M50
63	1	GA4M63
75	1	GA4M75
90	1	GA4M90
110	1	GA4M110

ELBOWS 45°

> SOCKET/SOCKET



GA8M32

Ø	Pack	Ref.
16	S10*	GA8M16
20	S10*	GA8M20
25	S10*	GA8M25
32	S10*	GA8M32
40	S10*	GA8M40
50	S10*	GA8M50
63	1	GA8M63
75	1	GA8M75
90	1	GA8M90
110	1	GA8M110

SERRATED STUB FLANGES

> SOCKET - DELIVERED WITHOUT FLAT GASKET



GACS75

Ø/øR	Pack	Ref.
50	S10*	GACS50
63	1	GACS63
75	1	GACS75
90	1	GACS90
110	1	GACS110

BENDS 90°

> SOCKET/SOCKET



GA4C75

Ø	Cond.	Ref.
50	S10*	GA4C50
63	1	GA4C63
75	1	GA4C75
90	1	GA4C90
110	1	GA4C110

COUPLINGS

> SOCKET/SOCKET



GAMA32

Ø	Pack	Ref.
16	S10*	GAMA16
20	S10*	GAMA20
25	S10*	GAMA25
32	S10*	GAMA32
40	S10*	GAMA40
50	S10*	GAMA50
63	1	GAMA63
75	1	GAMA75
90	1	GAMA90
110	1	GAMA110

CAPS

> SOCKET



GABO32

Ø	Pack	Ref.
16	S10*	GABO16
20	S10*	GABO20
25	S10*	GABO25
32	S10*	GABO32
40	S10*	GABO40
50	S10*	GABO50
63	1	GABO63
75	1	GABO75
90	1	GABO90
110	1	GABO110

* Unpackaging with additional cost