





Fittings



The use of anaerobic resins as a sealant for threaded joints is strictly forbidden.

REDUCING BUSHES LONG PATTERN				REDUCING BUSHES SHORT PATTERN				
> SPIGOT (Ø) / SOCKET (ØR)				> SPIGOT (Ø) / SOCKET (ØR)				
	Ø/ØR	Pack	Ref.		Ø/ØR	Pack	Ref.	
 GARD3220	25/16	S10*	GARD2516	 GARS32	20/16	S10*	GARS20	
	32/20	S10*	GARD3220		25/20	S10*	GARS25	
	40/25	S10*	GARD4025		32/25	S10*	GARS32	
	50/32	S10*	GARD5032		40/32	S10*	GARS40	
	63/32	1	GARD6332		50/40	S10*	GARS50	
	63/40	1	GARD6340		63/50	1	GARS63	
	75/32	1	GARD7532		75/63	1	GARS75	
	90/50	1	GARD9050		90/75	1	GARS90	
	90/63	1	GARD9063		110/90	1	GARS110	
	110/50	1	GARD1150					
	110/63	1	GARD1163					

Reducer's large ends for references GARD 32 to 110 (except GARD 7532) can be used as sockets and Spigotots, with one size interval. Small ends are socket only. Example: GARD 90/63 = 90 Spigot. + 75 Socket / 63 Socket

REDUCING TEES 90°				EQUAL TEES 90°				
> SOCKET/SOCKET				> SOCKET/SOCKET				
	Ø/ØR	Pack	Ref.		Ø	Pack	Ref.	
 GATR3220	20/16	S10*	GATR2016	 GATE32	16	S10*	GATE16	
	25/16	S10*	GATR2516		20	S10*	GATE20	
	25/20	S10*	GATR2520		25	S10*	GATE25	
	32/16	S10*	GATR3216		32	S10*	GATE32	
	32/20	S10*	GATR3220		40	S10*	GATE40	
	32/25	S10*	GATR3225		50	S10*	GATE50	
	40/20	S10*	GATR4020		63	1	GATE63	
	40/25	S10*	GATR4025		75	1	GATE75	
	40/32	S10*	GATR4032		90	1	GATE90	
	50/25	S10*	GATR5025		110	1	GATE110	
	50/32	S10*	GATR5032					
	50/40	S10*	GATR5040					
	63/25	1	GATR6325					
	63/32	1	GATR6332					
	63/40	1	GATR6340					
	75/25	1	GATR7525					
	75/32	1	GATR7532					
90/25	1	GATR9025						

Threaded fittings

THREADED ADAPTORS				EQUAL THREADED TEES 90°				
> SOCKET - FEMALE THREAD, WITH METAL REINFORCING RING				> SOCKET - FEMALE THREAD BRANCH, WITH METAL REINFORCING RING				
	Ø x G	Pack	Ref.		Ø x G	Pack*	Ref.	
 GAMM32	16 x 3/8"	S10*	GAMM16	 GATG2012	16 x 1/2"	S10	GATG1612	
	20 x 1/2"	S10*	GAMM20		20 x 1/2"	S10	GATG2012	
	25 x 3/4"	S10*	GAMM25		25 x 3/4"	S10	GATG2534	
	32 x 1"	S10*	GAMM32					
	40 x 1 1/4"	S10*	GAMM40					
	50 x 1 1/2"	S10*	GAMM50					
	63 x 2"	1	GAMM63					

Exclusively for assemblies with plastic threaded fittings
GAMM cold welding ends can also be used as Spigots with one size interval. Example: GAMM16 = 16 Socket / 20 Spigot.