






Brass threaded fittings for high torque

The use of anaerobic resins as a sealant for threaded joints is strictly forbidden.

THREADED ADAPTORS				THREADED ELBOW 90°				
> SOCKET/SPIGOT - FEMALE BRASS THREAD				> SOCKET - FEMALE BRASS THREAD				
	Ø (F/M) x G	Pack	Ref.		Ø (F/M) x G	Pack*	Ref.	
 GAMML32	16/20 x 3/8"	S5*	GAMML16	 GA4GL20	20 x 1/2"	S5	GA4GL20	
	20/25 x 1/2"	S5*	GAMML20					
	25/32 x 3/4"	S5*	GAMML25					
	32/40 x 1"	S5*	GAMML32					
	40/50 x 1"1/4	1	GAMML40					
	50/63 x 1"1/2	1	GAMML50					
	63/75 x 2"	1	GAMML63					
ADAPTOR NIPPLES				ADAPTOR NIPPLES				
> SOCKET/SPIGOT - MALE BRASS THREAD				> SOCKET/SPIGOT - MALE BRASS THREAD				
	Ø (F/M) x F	Pack	Ref.		Ø (F/M) x F	Pack*	Ref.	
 GAEAL32	16/20 x 3/8"	S5*	GAEAL16	 GAEBL25	16/20 x 1/2"	S5	GAEBL16	
	20/25 x 1/2"	S5*	GAEAL20		25/32 x 1"	S5	GAEBL25	
	25/32 x 3/4"	S5*	GAEAL25					
	32/40 x 1"	S5*	GAEAL32					
	40/50 x 1"1/4	1	GAEAL40					
	50/63 x 1"1/2	1	GAEAL50					
	63/75 x 2"	1	GAEAL63					

Fittings

WALL PLATE ELBOW				ACCESSORIES (ISO 4 414)			
> INLET MALE THREAD F - OUTLET FEMALE THREAD G FOR JOINTING ON PIPE WITH GAUR BRASS CONNECTOR				> MALE THREADED INSTANT FITTING PROFILE: ISO C - Ø INT.: 6 MM			
	f x G	Pack	Ref.		Ø	Pack	Ref.
 GAAP16	1/2" x 3/8"	1	GAAP16	 GHRR12	3/8"	1	GHRR38
	3/4" x 1/2"	1	GAAP20		1/2"	1	GHRR12
	1" x 3/4"	1	GAAP25				
QUICK ADAPTOR: ISO C							
> QUICK NIPPLES FOR Ø 8 MM FLEXIBLE PIPES - Ø INT.: 6 MM							
	Ø	Cond.	Ref.				
	8	1	GHES8				
DROP BENDS 180°				DROP BENDS			
> SPIGOT/SPIGOT (PROFILE P)				> SPIGOT/SPIGOT (PROFILE S)			
	Ø	Pack*	Ref.		Ø	Pack	Ref.
 GA2C20	16	S10	GA2C16	 Q2S20	20	1	Q2S20
	20	S10	GA2C20				
	25	S10	GA2C25				
	32	S5	GA2C32				