

Pipes - Fittings

PIPES

> CHAMFERED AT BOTH ENDS, IN 4 METER LENGTHS, PN10 FROM Ø 20 TO Ø 160, PN6 Ø 200. Wrapped in plastic sleeves



TUBF40

DN (outside Ø)	Pipe length (m)	Min. Wall Thickness (mm)	Pack (Lg)	Ref.
20	4	2,3	10*	TUBF20
25	4	2,3	10*	TUBF25
32	4	2,4	10*	TUBF32
40	4	3,0	10*	TUBF40
50	4	3,7	5*	TUBF50
63	4	4,7	3*	TUBF63
75	4	5,6	2	TUBF75
90	4	6,7	1	TUBF90
110	4	8,1	1	TUBF110
160	4	11,8	1	TUBF160
200	4	11,9	1	TUBF200

ELBOWS 90°

> SOCKET/SOCKET



F4M50

Ø	Pack	Ref.
20	S10*	F4M20
25	S10*	F4M25
32	S10*	F4M32
40	S10*	F4M40
50	S10*	F4M50
63	1	F4M63
75	1	F4M75
90	1	F4M90
110	1	F4M110
160	1	F4M160
200	1	F4M200

ELBOWS 45°

> SOCKET/SOCKET



F8M32

Ø	Pack	Ref.
20	S10*	F8M20
25	S10*	F8M25
32	S10*	F8M32
40	S10*	F8M40
50	S10*	F8M50
63	1	F8M63
75	1	F8M75
90	1	F8M90
110	1	F8M110
160	1	F8M160
200	1	F8M200

ELBOWS 90° WITH THREADED BRASS INSERT

> SOCKET/SOCKET - FEMALE BRASS THREAD



F4MI5012

Ø x G	Pack	Ref.
50 x 1/2"	1	F4MI5012
63 x 1/2"	1	F4MI6312

COUPLINGS

> SOCKET/SOCKET



FMA50

Ø	Pack	Ref.
20	S10*	FMA20
25	S10*	FMA25
32	S10*	FMA32
40	S10*	FMA40
50	S10*	FMA50
63	1	FMA63
75	1	FMA75
90	1	FMA90
110	1	FMA110
160	1	FMA160
200	1	FMA200

PLAIN NIPPLES

> SPIGOT/SPIGOT



FMC25

Length in mm	Pack*	Ref.
20 x 37	S10	FMC20
25 x 42	S10	FMC25

* Unpackaging with additional cost